



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-4360BP0116

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	TECO s.r.l. Via Sandro Pertini 39/41, I-25050 Provaglio d'Iseo (BS)
Distributor <i>Vertreiber</i>	TECO s.r.l. Via Sandro Pertini 39/41, I-25050 Provaglio d'Iseo (BS)
Product Category <i>Produktart</i>	gas fittings: Gas flow monitor (4360)
Product Description <i>Produktbezeichnung</i>	gas flow governor type K and M for the domestic gas-installation with over-flow-aperture
Model <i>Modell</i>	GST...
Test Reports <i>Prüfberichte</i>	laboratory control test: 21-0083-KP01-312 from 14.09.2021 (EBI) type testing: 07/310/4360/980 from 13.02.2008 (EBI)
Test Basis <i>Prüfgrundlagen</i>	DVGW VP 305-1 (01.12.2007)

Date of Expiry / File No. 23.03.2023 / 22-0043-GNV
Ablaufdatum / Aktenzeichen

70029304-1A-DE

30.03.2022 Kö A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases according to G 260: 03.2013	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
GST/L 2; GST/EFV; GST L2-V2	operation pressure: 15...100 mbar nominal flow rate: 1,3/2,0 m³/h nominal diameter: DN 15	
GST/L 2; GST/EFV; GST L2-V2	operation pressure: 15...100 mbar nominal flow rate: 1,3/2,0/3,2 m³/h nominal diameter: DN 20	
GST/L 2; GST/EFV; GST/LDW; GST/LUP; GST L2-V2; GST L2-B	operation pressure: 15...100 mbar nominal flow rate: 1,3 /2,0/3,2/4,8 m³/h nominal diameter: DN 25	GST L2-B only with nominal flow rates 2,0/3,2/4,8 m³/h
GST/L 2; GST/EFV; GST L2-V2	operation pressure: 15...100 mbar nominal flow rate: 8,0 m³/h nominal diameter: DN 32	
GST/L 2; GST/EFV; GST L2-V2	operation pressure: 15...100 mbar nominal flow rate: 8,0/12,8 m³/h nominal diameter: DN 40	
GST/L 2; GST/EFV; GST L2-V2	operation pressure: 15...100 mbar nominal flow rate: 12,8 m³/h nominal diameter: DN 50	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
GST/LDW GST/LUP GST/EFV	type K and M according to DVGW-VP 305-1; orientation of installation: vertical downward type K and M according to DVGW-VP 305-1; orientation of installation: vertical upward type K according to DVGW-VP 305-1, with plastic lock-up body; orientations of installation: vertical upward and horizontal
GST/L2	type K acc. to DVGW-VP 305-1 by orientation of installation horizontal; type M acc. to DVGW-VP 305-1 for flue rates 2,0 up to 12,8 m³/h (air) by orientation of installation vertical upward
GST/L2-V2 GST/L2-B	type K according to DVGW-VP 305-1; orientation of installation: horizontal / vertical upward type K according to DVGW-VP 305-1 as integral inset, with plastic disc; mounting position: vertical upward, vertical downward and horizontal

certified Components

zertifizierte Bauteile / Werkstoffe

Registr. No. <i>Registrier-Nr.</i>	Component <i>Bauteil (Produktart)</i>	Model/Type <i>Modell/Typ</i>	Manufacturer <i>Hersteller</i>
NG-5112BM0548	Elastomer material for seals in gas appliances	01/H70 NBR/01/H70 NBR	LAV.EL GOMMA S.r.l.

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

ambient temperature range: -20...+60 °C

connections: at one side internal thread Rp 1/2... Rp 2, at the other side external thread, in each case according to DIN EN 10226-1

